



Verified Scalability Guide for Cisco Nexus Dashboard Fabric Controller, Release 12.0.2f

[Cisco Nexus Dashboard Fabric Controller Verified Scalability](#) 2

[Verified Scale Limits for Release 12.0.2f](#) 2

[Full Cisco Trademarks with Software License](#) ?

Revised: April 22, 2022

Cisco Nexus Dashboard Fabric Controller Verified Scalability

Verified Scale Limits for Release 12.0.2f

This section provides verified scalability values for various deployment types for Cisco Nexus Dashboard Fabric Controller, Release 12.0.2f.

The values are validated on testbeds that are enabled with a reasonable number of features and aren't theoretical system limits for Cisco Nexus Dashboard Fabric Controller software or Cisco Nexus/MDS switch hardware and software. When you try to achieve maximum scalability by scaling multiple features at the same time, results might differ from the values that are listed here.

Cisco NDFC, Release 12.0.2f supports 150 switches per fabric and 350 switches across the entire NDFC service.

Nexus Dashboard Server Resource (CPU/Memory) Requirements

Table 1: Server Resource (CPU/Memory) Requirements to run NDFC on top of ND

Deployment Type	Node Type	CPUs	Memory	Storage (Throughput: 40-50MB/s)
Fabric Discovery	Virtual Node (vND) – app OVA	16vCPUs	64GB	550GB SSD
	Physical Node (pND) (PID: SE-NODE-G2)	2x 10-core 2.2G Intel Xeon Silver CPU	256 GB of RAM	4x 2.4TB HDDs 400GB SSD 1.2TB NVME drive
Fabric Controller	Virtual Node (vND) – app OVA	16vCPUs	64GB	550GB SSD
	Physical Node (pND) (PID: SE-NODE-G2)	2x 10-core 2.2G Intel Xeon Silver CPU	256 GB of RAM	4x 2.4TB HDDs 400GB SSD 1.2TB NVME drive

Deployment Type	Node Type	CPUs	Memory	Storage (Throughput: 40-50MB/s)
SAN Controller	Virtual Node (vND) – app OVA (without SAN Insights)	16vCPUs	64GB	550GB SSD
	Data Node (vND) – Data OVA (with SAN Insights)	32vCPUs	128GB	3TB SSD
	Physical Node (pND) (PID: SE-NODE-G2)	2x 10-core 2.2G Intel Xeon Silver CPU	256 GB of RAM	4x 2.4TB HDDs 400GB SSD 1.2TB NVME drive

Scale Limits for Fabric Controller

Table 2: Scale Limits for Fabric Controller Deployment

Profile	Deployment Type	Verified Limit
Fabric Controller (Non-Production)	1-Node vND (app OVA)	<= 25 switches (Non-Production)
Fabric Controller	3-Node vND (app OVA)	80 Switches
Fabric Controller	3-Node pND (SE)	350 Switches
Fabric Controller	5-Node vND (app OVA)	350 Switches

Scale Limits for Fabric Discovery

Table 3: Scale Limits for Fabric Discovery Deployment

Profile	Deployment Type	Verified Limit
Fabric Discovery	1-Node vND (app OVA)	<= 25 switches (Non-Production)
Fabric Discovery	3-Node vND (app OVA)	80 Switches
Fabric Discovery	3-Node pND (SE)	350 Switches
Fabric Discovery	5-Node vND (app OVA)	350 Switches

Table 4: Scale Limits For Provisioning New VXLAN EVPN Fabrics (Also referred to as "Greenfield" Deployment)

Description	Verified Limit
Fabric Underlay Overlay	
Switches per fabric	150

Description	Verified Limit
Physical Interfaces	30000
Layer-3 scenario: Networks	1000
Layer 2 scenario: Networks	1500
Layer-3 scenario: VRFs	500 Note 500 VRFs over 1000 Layer-3 network or 500 VRFs over 1500 Layer-2 network is supported.
VRF instances for external connectivity	300
Endpoint Locator	
Endpoints	50000
IPAM Integrator application	150 networks with a total of 4K IP allocations on the Infoblox server
Multi-Site Domain	
Sites	13

Refer to the following table if you are transitioning a Cisco Nexus 9000 Series switches based VXLAN EVPN fabric management to NDFC. Before the migration, your fabric was an NFM managed or CLI configured fabric.

Table 5: Scale Limits For Transitioning Existing Fabric Management to DCNM (Also referred to as "Brownfield Migration")

Description	Verified Limit
Fabric Underlay and Overlay	
Switches per fabric	100
Physical Interfaces	5000
VRF instances	100
Overlay networks	500
VRF instances for external connectivity	100
Endpoint Locator	
Endpoints	50000
IPAM Integrator application	150 networks with a total of 4K IP allocations on the Infoblox server

Scale Limits for IPFM Fabrics

Table 6: Scale Limits for IPFM Fabrics

Description	Verified Limit
Number of nodes	35 (2 spines and 33 leafs)
Number of routes	32000

Description	Verified Limit
Host Policy	
Sender	8000
Receiver	8000
PIM	512
Flow Policy	2000
ASM group-range	20
NBM Static Flows	
Per switch maximum (receiver leaf where the static OIF will be programmed) mroutes	1500
Per fabric maximum mroutes	8000
VRFs	16
RTP Flow Monitoring with ACL	
ACL	128 IPv4 ACL entries or 64 IPv6 entries (total 128 TCAM spaces) Note With combined IPv4 and IPv6 ACL entries, scale limit cannot exceed 128 TCAM spaces.

Scale Limits for SAN Controller

Table 7: Scale Limits for SAN Controller (without SAN Insights)

Profile	Deployment Type	Verified Limit
SAN Controller	1-Node vND (app OVA)	80 Switches, 20K Ports
SAN Controller	3-Node vND (app OVA)	80 Switches, 20KPorts

Table 8: Scale Limits for SAN Controller (with SAN Insights)

Profile	Deployment Type	Verified Limit
SAN Controller	1-Node vND (data OVA)	120K ITLs/ITNs
SAN Controller	1-Node pND (SE)	120K ITLs/ITNs
SAN Controller	3-Node vND (data OVA)	150K ITLs/ITNs
SAN Controller	3-Node pND (SE)	250K ITLs/ITNs

THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS MANUAL ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS MANUAL ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

THE SOFTWARE LICENSE AND LIMITED WARRANTY FOR THE ACCOMPANYING PRODUCT ARE SET FORTH IN THE INFORMATION PACKET THAT SHIPPED WITH THE PRODUCT AND ARE INCORPORATED HEREIN BY THIS REFERENCE. IF YOU ARE UNABLE TO LOCATE THE SOFTWARE LICENSE OR LIMITED WARRANTY, CONTACT YOUR CISCO REPRESENTATIVE FOR A COPY.

The Cisco implementation of TCP header compression is an adaptation of a program developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. All rights reserved. Copyright © 1981, Regents of the University of California.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED "AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

All printed copies and duplicate soft copies of this document are considered uncontrolled. See the current online version for the latest version.

Cisco has more than 200 offices worldwide. Addresses and phone numbers are listed on the Cisco website at www.cisco.com/go/offices.

The documentation set for this product strives to use bias-free language. For purposes of this documentation set, bias-free is defined as language that does not imply discrimination based on age, disability, gender, racial identity, ethnic identity, sexual orientation, socioeconomic status, and intersectionality. Exceptions may be present in the documentation due to language that is hardcoded in the user interfaces of the product software, language used based on standards documentation, or language that is used by a referenced third-party product.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/c/en/us/about/legal/trademarks.html>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1721R)

© 2021 Cisco Systems, Inc. All rights reserved.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA 95134-1706
USA

Asia Pacific Headquarters
CiscoSystems(USA)Pte.Ltd.
Singapore

Europe Headquarters
CiscoSystemsInternationalBV
Amsterdam,TheNetherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.