

## Dell Micro-portable Projectors 2200MP, 3300MP and 4100MP



## Dell | Projectors

**Great things come in small packages,  
and they keep getting better.**

Whether for business, education or personal use, Dell™ projectors offer great performance at an affordable price. They are packed with high-end technology and include the extras as standard, so you have everything you need to get up and running, right out of the box – custom-fitted hard-shell carrying case, remote control and data/video cables.

### Deliver bright, clear images

Dell projectors use advanced DLP™ (Digital Light Processing™) technology from Texas Instruments to achieve great picture quality in a small and light form factor. They combine consistent brightness and high contrast ratios to produce clear, sharp video and text images. Built-in digital keystone correction and zoom help you adjust the projector for optimal viewing for almost any situation. Dell offers a choice of native resolutions so you can select the projector to match your requirements and budget.

### Outstanding ease of use

Dell Projectors are extremely easy to use. With support for a wide range of input video sources and television and video standards, you get great presentation flexibility. The projectors feature automatic synchronisation so the projector will detect the type of input and change its settings accordingly. This plug-and-play technology makes the projectors compatible with most computers, including Dell Latitude™ and Inspiron™ notebooks – just follow the simple Quick Set Up guide and you're ready to go.



Dell 2200MP Projector

### Excellent mobility features

Dell projectors are small and light – they weigh less and are more portable than many notebook computers. They're built for durability, with a sturdy magnesium casing. The included carrying case makes travelling easy. With desktop or ceiling mount capability and front and rear projection, you can use these projectors just about anywhere.

### Perfect for work and entertainment

Dell projectors have enough performance features to be your workhorse during the week, but at the weekend these units can take home entertainment to the next level as an excellent complement to your home theatre system for watching movies, sporting events, viewing photos or even playing video games.

### Great value is a given – it's from Dell!

Like all Dell products, Dell projectors maximise price-for-performance value. They are affordably priced and backed by Dell service and support. Valuable extras, such as a carrying case and remote control, are included at no extra charge.



Dell 3300MP Projector



Dell 4100MP Projector

**Presentations made easy. Easy as**



Visit [www.euro.dell.com](http://www.euro.dell.com) for more information.



# Dell Micro-portable Projectors 2200MP, 3300MP and 4100MP



Model Name  
Projection Technology  
Brightness  
Native Resolution  
Max. Sync Resolution  
Contrast Ratio  
Displayable Colours  
Image Adjustment

Projection Lens  
Zoom  
Memory Card Reader  
Keystone Correction  
Projection Screen Size  
Projection Distance  
Video Compatibility

Horizontal Frequency  
Vertical Frequency  
Internal Loudspeaker

Bulb Type  
Bulb Lifetime  
Power Supply  
Power Consumption  
Power Saver Shutdown  
I/O Connectors

Power  
Computer Input

Monitor Loop-through  
Video Input

Audio Input  
Control Input/Output

Environmental  
Operating Temperature  
Operating Humidity  
Storage Temperature  
Storage Humidity

Flexible orientation

Included Accessories

Optional Accessories  
Weight  
Dimensions (h x w x d)  
Warranty

## 4100MP

|                                                                                                                            |
|----------------------------------------------------------------------------------------------------------------------------|
| Single chip DLP™ DDR technology                                                                                            |
| 2200 ANSI Lumens (max) <sup>3</sup>                                                                                        |
| XGA (1024 X 768)                                                                                                           |
| UXGA (1600 x 1200)                                                                                                         |
| 2000:1 (Full On/Full Off)                                                                                                  |
| 16.7 million                                                                                                               |
| Zoom, focus and horizontal and auto vertical keystone controls                                                             |
| F/2.43~2.66 , f=28.0~33.6mm                                                                                                |
| 1.2x manual zoom                                                                                                           |
| Optional 6-in-1 reader                                                                                                     |
| ±16° adjustment                                                                                                            |
| 24.4-292.5" (0.6-7.4m diagonal)                                                                                            |
| 1.2m – 12m                                                                                                                 |
| NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM and HDTV (480i/P, 576i/P, 720P and 1080i) Composite Video and S-Video capability |
| 15kHz-100kHz                                                                                                               |
| 43Hz-120Hz                                                                                                                 |
| Two 2-watt speakers                                                                                                        |
| 250-watt, user-replaceable UHP lamp                                                                                        |
| 1500 hours (up to 3000 hours in Eco-mode)                                                                                  |
| Universal 90-240V AC 50-60 Hz                                                                                              |
| 310W at full power                                                                                                         |
| Yes                                                                                                                        |

|                                                                               |
|-------------------------------------------------------------------------------|
| AC power input socket                                                         |
| One M1-DA for analogue/digital/HDTV; one D-sub 15-pin for analogue/HDTV input |
| One 15-pin D-sub                                                              |
| One composite video (RCA); one S-Video and one 3-pin component for HDTV       |
| One 3.5mm phone jack for line audio input                                     |
| One DC jack 12 volt @ 200mA output, relay control. One mini-DIN RS-232 input  |

|                              |
|------------------------------|
| 5°C – 35°C (41°F to 95°F)    |
| 80% maximum                  |
| -20°C to 60°C (4°F to 140°F) |
| 80% maximum                  |

Desktop or ceiling mountable and rear or front projection

Carrying case, wireless remote with laser pointer, M1-DA to D-sub/USB cable, S-Video cable, RCA audio composite video cable, composite video cable, composite cable, miniphone jack, power cord, quick start guide and user manual

|                                     |
|-------------------------------------|
| Ceiling mount kit, Replacement bulb |
| 2.95kg                              |
| 302 x 251 x 114mm                   |
| Two years (90 days on bulb)         |

## 3300MP

|                                                                                                                         |
|-------------------------------------------------------------------------------------------------------------------------|
| Single chip DLP DDR technology                                                                                          |
| 1500 ANSI Lumens (max) <sup>2</sup>                                                                                     |
| XGA (1024 x 768)                                                                                                        |
| SXGA+ (1400 x 1050)                                                                                                     |
| 1700:1 (Full On/Full Off)                                                                                               |
| 16.7 million                                                                                                            |
| Zoom, focus and auto vertical keystone controls                                                                         |
| F/2.43~2.65 , f=28.04~33.59mm                                                                                           |
| 1.2x manual zoom                                                                                                        |
| Optional 6-in-1 reader                                                                                                  |
| ±16° adjustment                                                                                                         |
| 24.4-292.5" (0.6-7.4m diagonal)                                                                                         |
| 1.2m – 12m                                                                                                              |
| NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, HDTV (480i/P, 576i/P, 720P and 1080i) Composite Video and S-Video capability |
| 15kHz-80kHz                                                                                                             |
| 50Hz-85Hz                                                                                                               |
| One 2-watt speaker                                                                                                      |
| 180-watt, user-replaceable P-VIP lamp                                                                                   |
| 3000 hours (up to 5000 hours in Eco-Mode)                                                                               |
| Universal 100-240V AC 50-60 Hz                                                                                          |
| 224W at normal operation                                                                                                |
| Yes                                                                                                                     |

|                                                                         |
|-------------------------------------------------------------------------|
| AC power input socket                                                   |
| One M1-DA for analogue/digital/HDTV                                     |
| One 15-pin D-sub                                                        |
| One composite video (RCA); one S-Video and one M1-DA for component HDTV |
| One 3.5mm phone jack for line audio input                               |
| One mini-DIN RS-232 input                                               |

|                              |
|------------------------------|
| 5°C – 35°C (41°F to 95°F)    |
| 80% maximum                  |
| -20°C to 60°C (4°F to 140°F) |
| 80% maximum                  |

Desktop or ceiling mountable and rear or front projection

Carrying case, wireless remote with laser pointer, M1-DA to D-sub/USB cable, S-Video cable, RCA audio composite video cable, composite video cable, composite cable, miniphone jack, power cord, quick start guide and user manual

|                                     |
|-------------------------------------|
| Ceiling mount kit, Replacement bulb |
| 1.81kg                              |
| 245 x 211 x 83.5mm                  |
| Two years (90 days on bulb)         |

## 2200MP

|                                                                                                                         |
|-------------------------------------------------------------------------------------------------------------------------|
| Single chip DLP DDR technology                                                                                          |
| 1200 ANSI Lumens (max) <sup>1</sup>                                                                                     |
| SVGA (800 x 600)                                                                                                        |
| SXGA+ (1400 x 1050)                                                                                                     |
| 1700:1 (Full On/Full Off)                                                                                               |
| 16.7 million                                                                                                            |
| Zoom, focus and keystone controls                                                                                       |
| F/2.4~2.7, f=19.7~23.6mm                                                                                                |
| 1.2x manual zoom                                                                                                        |
| None                                                                                                                    |
| ±16° adjustment                                                                                                         |
| 28-337" (0.7-8.6m) diagonal                                                                                             |
| 1.2m-12m                                                                                                                |
| NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, HDTV (480i/P, 576i/P, 720P and 1080i) Composite Video and S-Video capability |
| 15kHz-70kHz                                                                                                             |
| 43Hz-85Hz                                                                                                               |
| One 2-watt speaker                                                                                                      |
| 200-watt, user-replaceable P-VIP lamp                                                                                   |
| 2000 hours (up to 2500 hours in Eco-Mode)                                                                               |
| Universal 100-240V AC, 50-60Hz                                                                                          |
| 250W at normal operation                                                                                                |
| Yes                                                                                                                     |

|                                               |
|-----------------------------------------------|
| AC power input socket                         |
| 15-pin D-sub for analogue RGB/component, HDTV |
| One 15-pin D-sub                              |
| One composite video RCA and one S-Video       |
| One 3.5mm phone jack for line audio input     |
| None                                          |

|               |
|---------------|
| 5°C to 35°C   |
| 80% maximum   |
| -20°C to 60°C |
| 80% maximum   |

Desktop or ceiling mountable and rear or front projection

Carrying case, wireless remote control, VGA cable (D-sub to D-sub), component video, S-video cable, USB cable, composite video cable, RCA to audio, mini-pin, power cord, quick start guide and user manual

|                                     |
|-------------------------------------|
| Ceiling mount kit, Replacement bulb |
| 2.1kg                               |
| 85mm x 266mm x 216mm                |
| One year (90 days on bulb)          |

Pricing, specifications, availability and terms may change without notice. Dell's Terms and Conditions of Sales and Service apply and are available on request and at [www.euro.dell.com](http://www.euro.dell.com). DLP and Digital Light Processing are trademarks of Texas Instruments, Incorporated. Dell, the Dell logo, Latitude and Inspiron are trademarks of Dell Computer Corporation. 1. Based on ANSI/NAPM IT7 228-1997 tests of 73 units, September 2003, with average ANSI Lumens 1118. Bulb brightness degrades with usage. Dell recommends replacing your bulb after 2000 hours of usage. 2. Based on ANSI/NAPM IT7 228-1997 tests of 15 units, January 2004, with average ANSI Lumens 1523. Bulb brightness degrades with usage. Dell recommends replacing your bulb after 3000 hours of usage (up to 5000 hours in Eco-mode). 3. Based on ANSI/NAPM IT7 228-1997 tests of 35 units, November 2003, with average ANSI Lumens 2144. Bulb brightness degrades with usage. Dell recommends replacing your bulb after 1500 hours of usage. © 2004 Dell Computer Corporation. All rights reserved. Reproduction in any manner whatsoever without the express written permission of Dell Computer Corporation is strictly forbidden.

EU865/25March2004

Presentations made easy. Easy as **DELL™**

Visit [www.euro.dell.com](http://www.euro.dell.com) for more information.