书本形式

封底内页 封底 封面 封面内页

120.00 mm

160.00 mm

PACKING LIST

Name	Quantity				Notes
	GVM-1380D	GVM-1380D-P	GVM-1380D-S	GVM-1380D-PS	
Photography Lights	1	2	3	1	
Power Cord	1	2	3	1	
Adapter	1	2	3	1	
Diffuser	1	2	3	1	
Barn Door	1	2	3	1	
Light Stand	1	2	3	1	
Carrying Case	1	1	1	1	
Instructions	1	1	1	1	

GVM

GREAT VIDEO MAKER

Scan to download App

Apple store: gvmled.com
Google Play: Search "GVM"
Support email: support@gvmled.com
Sales email: sales@gvmled.com
Website: www.gvmled.com or www.gvmsdk.com

GVM

GVM-1380D / GVM-1380D-P

CONTENTS

Product Introduction ..... Page 1
Disclaimers ..... Page 1
Product Detail GVM-1380D ..... Page 2
Product Detail GVM-1380D ..... Page 3
Product Structure Analysis ..... Page 4
Installation method ..... Page 5
Accessories installation method ..... Page 6
Description of product control keys ..... Page 7
Function introduction and instruction for use ..... Page 10-13
Precautions ..... Page 13
APP control and multiple units control ..... Page 14
Use and preservation ..... Page 15
Simple faults and troubleshooting ..... Page 15-16
Packing list ..... Page 17

PRODUCT INTRODUCTION

Welcome to GVM-1380D/GVM-1380D-P. This product is specially designed for remote photography professionals. The product is intended for film / outdoor / studio photography and suits for Youtube video shooting. The main features of the product are:

① Adopt high-power LED light source, with color temperature 5600K, color temperature adjustable from 2700K-6500K and color rendering index (CRI) and color fidelity (TLCI) reaches 95 and 96 respectively, which is helpful to restore the true color of objects and provide very clear and vivid shooting effect.

② Adopt intelligent control system, which can be controlled by your intelligent mobile device through the APP software installed on your mobile phone, and can also be controlled by remote the light. You can also install fixing pole with light stand to avoid shaking light, make the light softer, and customize the RGB light, allowing you to easily and smoothly complete the shooting.

③ The product can be installed in three ways: tripod, ceiling, Frame, can be changed to 75 degrees light. Party, disco, Fireplace.

We believe that once using our product carefully, you will make huge progress when shooting. Before using the product, you are strongly recommended to read the instructions carefully.

DISCLAIMERS

1. Before using the product, please read the instructions carefully and make sure you use the product correctly. If you don't read the instructions and damage, you will be responsible for it. If the product is unsafe or incorrect, we strongly recommend stop using the product.
2. Once you use the product, you are deemed to have read the disclaimer and agreeing to be responsible for the consequences of the product operation. If you do not agree and unwilling to take full responsibility for the use of the product and possible consequences.

PRODUCT DETAIL GVM-1300D

- Brand: GVM
- Product Name: Photography Light
- Product model: GVM-1300D
- Product Type: Photography lift light
- Functions/features: APP (Bluetooth connection), brand new LED screen, joint control, high display finger lamp beads, multiple scene modes
- Lamp beads quantity: 1056pcs
- Color rendering index: ≥97
- Color temperature adjustable: 2700K-6500K
- Brightness: 2700lux/0.5m, 1050lux/1m
- Light-adjustment method: Step less adjustment
- Product net weight: 1.8-5.6L
- Product size (mm): 270*187*42-580
- Power: 60W
- Voltage: AC100-240V
- Power supply mode: DC input & battery
- Battery capacity: 7.4V-6400mAh/47.3
- Power supply: DC: 15V/3A
- Heat dissipation: Natural heat dissipation
- Product material: aluminum alloy
- Piece of Gift box: 12pcs, Hardcoa

PRODUCT DETAIL GVM-1500D

- Brand: GVM
- Product Name: Photography Light
- Product model: GVM-1500D
- Product Type: Photography lift light
- Functions/features: APP (Bluetooth connection), brand new LED screen, joint control, high display finger lamp beads, multiple scene modes
- Lamp beads quantity: 1728pcs
- Color rendering index: ≥97
- Color temperature adjustable: 2700K-6500K
- Brightness: 2700lux/0.5m, 1350lux/1m
- Light-adjustment method: Step less adjustment
- Product net weight: 1.8-5.6L
- Product size (mm): 270*187*42-580
- Power: 80W
- Voltage: AC100-240V
- Power supply mode: DC input & battery
- Battery capacity: 7.4V-6400mAh/47.3
- Power supply: DC: 15V/3A
- Heat dissipation: Natural heat dissipation
- Product material: aluminum alloy
- Piece of Gift box: 12pcs, Hardcoa

PRODUCT STRUCTURE ANALYSIS

INSTALLATION METHOD

① The lamp can be installed and fixed on the bracket by rotating the knob clockwise, and unloaded by rotating it the counterclockwise direction.

② Insert the diffuser from the side of the light panel

③ Loosen the adjustment knobs on both sides of the U-bracket, adjust the angle of the panel you need, and then tighten the adjustment knobs on both sides of the U-bracket.



④ There are two power supply modes to choose:
① Connect the power cord to the power socket to adapt to AC power supply.
② Purchase two other suitable lithium batteries and put them for power supply.
NOTE: 1. Lithium Battery not included in product.

ACCESSORIES INSTALLATION METHOD

Please read the instructions carefully before installation and use the product correctly.

Light control fastling :

Light control fastling can control the angle of light.
Align the fixing knob(ring) holes with the screw holes of the hinges and lock the screws with screwed.



DESCRIPTION OF PRODUCT CONTROL KEYS

Battery Cover
Battery Slot
Battery Cover Locking Button
Battery Cover Locking Button
Battery Cover Locking Button