

SPLIT-CORE CURRENT TRANSFORMERS FOR THE UMG 20CM, TYPE SC-CT-20, CLASS 1

Split-core current transformers are suitable for quick and safe installation in existing systems and offer transformer ratios from 3000/1 to 6000/1. They are only compatible with the UMG 20CM.



SPLIT-CORE CURRENT TRANSFORMER FOR THE UMG 20CM, TYPE SC-CT-20 – TECHNICAL DATA

SPLIT-CORE CURRENT TRANSFORMER, TYPE SC-CT-20							
TYPE	MAX. OPERATING CURRENT in A	RATIO	MAX Ø OF PRIMARY CONDUCTOR in mm	CLASS	DIMENSIONS in mm (W x H x D)	WEIGHT in kg	PART NO.
SC-CT-20*	63	3000/1	10	1	approx. 32 x 41.4 x 32.3	0.04	15.03.092
INDIVIDUAL ACCESSORIES (LOAD IS INCLUDED IN THE SCOPE OF DELIVERY WITH THE SC-CT-20)							
Load (3.9 Ω) for SC-CT-20 operating current transformers with 1.5 m connection cable and spring terminal							15.03.086

* Incl. prefabricated connecting cable; 1.5 m with load and spring terminal for operating current measurement

**SPLIT-CORE CURRENT TRANSFORMER FOR THE UMG 20CM, TYPE SC-CT-20 –
DIMENSIONAL DRAWINGS**

