


HITCH BALL WITH 1" SHANK

INSTALLATION INSTRUCTIONS


 **WARNING:** Read and observe all warnings, instructions, and capacity limitations before using this product. Failure to comply with this warning and the associated instructions and capacity limitations may result in serious personal injury and/or significant property damage.

1. Choose ball diameter based on the Coupler rating.
2. The weight rating of the ball should match or exceed the trailer rating.
3. Install correct Hitch Ball so that the diameter matches the Coupler size:
 - The shank should be long enough to exceed the Ball Mount bar thickness and a tightened nut by 2-1/2 threads.
 - The diameter of the shank should match the tongue hole diameter.
4. Torque nut with locking washer to 250 ft lbs.

IF YOU EXPERIENCE ANY PROBLEMS WITH YOUR TOWSMART PRODUCT DO NOT RETURN THE UNIT TO THE RETAILER FROM WHICH IT WAS PURCHASED. INSTEAD, PLEASE CALL 1-844-295-9215 FOR ASSISTANCE WITH ANY PROBLEMS. WARRANTY INFORMATION IS AVAILABLE UPON REQUEST AND CAN BE FOUND ONLINE AT WWW.TOWSMART.COM.

HITCH BALL WITH 1" SHANK

INSTALLATION INSTRUCTIONS


 **WARNING:** Read and observe all warnings, instructions, and capacity limitations before using this product. Failure to comply with this warning and the associated instructions and capacity limitations may result in serious personal injury and/or significant property damage.

1. Choose ball diameter based on the Coupler rating.
2. The weight rating of the ball should match or exceed the trailer rating.
3. Install correct Hitch Ball so that the diameter matches the Coupler size:
 - The shank should be long enough to exceed the Ball Mount bar thickness and a tightened nut by 2-1/2 threads.
 - The diameter of the shank should match the tongue hole diameter.
4. Torque nut with locking washer to 250 ft lbs.

IF YOU EXPERIENCE ANY PROBLEMS WITH YOUR TOWSMART PRODUCT DO NOT RETURN THE UNIT TO THE RETAILER FROM WHICH IT WAS PURCHASED. INSTEAD, PLEASE CALL 1-844-295-9215 FOR ASSISTANCE WITH ANY PROBLEMS. WARRANTY INFORMATION IS AVAILABLE UPON REQUEST AND CAN BE FOUND ONLINE AT WWW.TOWSMART.COM.

HITCH BALL WITH 1" SHANK

INSTALLATION INSTRUCTIONS


 **WARNING:** Read and observe all warnings, instructions, and capacity limitations before using this product. Failure to comply with this warning and the associated instructions and capacity limitations may result in serious personal injury and/or significant property damage.

1. Choose ball diameter based on the Coupler rating.
2. The weight rating of the ball should match or exceed the trailer rating.
3. Install correct Hitch Ball so that the diameter matches the Coupler size:
 - The shank should be long enough to exceed the Ball Mount bar thickness and a tightened nut by 2-1/2 threads.
 - The diameter of the shank should match the tongue hole diameter.
4. Torque nut with locking washer to 250 ft lbs.

IF YOU EXPERIENCE ANY PROBLEMS WITH YOUR TOWSMART PRODUCT DO NOT RETURN THE UNIT TO THE RETAILER FROM WHICH IT WAS PURCHASED. INSTEAD, PLEASE CALL 1-844-295-9215 FOR ASSISTANCE WITH ANY PROBLEMS. WARRANTY INFORMATION IS AVAILABLE UPON REQUEST AND CAN BE FOUND ONLINE AT WWW.TOWSMART.COM.

HITCH BALL WITH 3/4" SHANK

INSTALLATION INSTRUCTIONS


 **WARNING:** Read and observe all warnings, instructions, and capacity limitations before using this product. Failure to comply with this warning and the associated instructions and capacity limitations may result in serious personal injury and/or significant property damage.

1. Choose ball diameter based on the Coupler rating.
2. The weight rating of the ball should match or exceed the trailer rating.
3. Install correct Hitch Ball so that the diameter matches the Coupler size:
 - The shank should be long enough to exceed the Ball Mount bar thickness and a tightened nut by 2-1/2 threads.
 - The diameter of the shank should match the tongue hole diameter.
4. Torque nut with locking washer to 160 ft lbs.

IF YOU EXPERIENCE ANY PROBLEMS WITH YOUR TOWSMART PRODUCT DO NOT RETURN THE UNIT TO THE RETAILER FROM WHICH IT WAS PURCHASED. INSTEAD, PLEASE CALL 1-844-295-9215 FOR ASSISTANCE WITH ANY PROBLEMS. WARRANTY INFORMATION IS AVAILABLE UPON REQUEST AND CAN BE FOUND ONLINE AT WWW.TOWSMART.COM.

HITCH BALL WITH 3/4" SHANK

INSTALLATION INSTRUCTIONS


 **WARNING:** Read and observe all warnings, instructions, and capacity limitations before using this product. Failure to comply with this warning and the associated instructions and capacity limitations may result in serious personal injury and/or significant property damage.

1. Choose ball diameter based on the Coupler rating.
2. The weight rating of the ball should match or exceed the trailer rating.
3. Install correct Hitch Ball so that the diameter matches the Coupler size:
 - The shank should be long enough to exceed the Ball Mount bar thickness and a tightened nut by 2-1/2 threads.
 - The diameter of the shank should match the tongue hole diameter.
4. Torque nut with locking washer to 160 ft lbs.

IF YOU EXPERIENCE ANY PROBLEMS WITH YOUR TOWSMART PRODUCT DO NOT RETURN THE UNIT TO THE RETAILER FROM WHICH IT WAS PURCHASED. INSTEAD, PLEASE CALL 1-844-295-9215 FOR ASSISTANCE WITH ANY PROBLEMS. WARRANTY INFORMATION IS AVAILABLE UPON REQUEST AND CAN BE FOUND ONLINE AT WWW.TOWSMART.COM.

HITCH BALL WITH 3/4" SHANK

INSTALLATION INSTRUCTIONS


 **WARNING:** Read and observe all warnings, instructions, and capacity limitations before using this product. Failure to comply with this warning and the associated instructions and capacity limitations may result in serious personal injury and/or significant property damage.

1. Choose ball diameter based on the Coupler rating.
2. The weight rating of the ball should match or exceed the trailer rating.
3. Install correct Hitch Ball so that the diameter matches the Coupler size:
 - The shank should be long enough to exceed the Ball Mount bar thickness and a tightened nut by 2-1/2 threads.
 - The diameter of the shank should match the tongue hole diameter.
4. Torque nut with locking washer to 160 ft lbs.

IF YOU EXPERIENCE ANY PROBLEMS WITH YOUR TOWSMART PRODUCT DO NOT RETURN THE UNIT TO THE RETAILER FROM WHICH IT WAS PURCHASED. INSTEAD, PLEASE CALL 1-844-295-9215 FOR ASSISTANCE WITH ANY PROBLEMS. WARRANTY INFORMATION IS AVAILABLE UPON REQUEST AND CAN BE FOUND ONLINE AT WWW.TOWSMART.COM.

HITCH BALL WITH 3/4" SHANK

INSTALLATION INSTRUCTIONS


 **WARNING:** Read and observe all warnings, instructions, and capacity limitations before using this product. Failure to comply with this warning and the associated instructions and capacity limitations may result in serious personal injury and/or significant property damage.

1. Choose ball diameter based on the Coupler rating.
2. The weight rating of the ball should match or exceed the trailer rating.
3. Install correct Hitch Ball so that the diameter matches the Coupler size:
 - The shank should be long enough to exceed the Ball Mount bar thickness and a tightened nut by 2-1/2 threads.
 - The diameter of the shank should match the tongue hole diameter.
4. Torque nut with locking washer to 160 ft lbs.

IF YOU EXPERIENCE ANY PROBLEMS WITH YOUR TOWSMART PRODUCT DO NOT RETURN THE UNIT TO THE RETAILER FROM WHICH IT WAS PURCHASED. INSTEAD, PLEASE CALL 1-844-295-9215 FOR ASSISTANCE WITH ANY PROBLEMS. WARRANTY INFORMATION IS AVAILABLE UPON REQUEST AND CAN BE FOUND ONLINE AT WWW.TOWSMART.COM.

HITCH BALL WITH 1-1/4" SHANK

INSTALLATION INSTRUCTIONS

 **WARNING:** Read and observe all warnings, instructions, and capacity limitations before using this product. Failure to comply with this warning and the associated instructions and capacity limitations may result in serious personal injury and/or significant property damage.

1. Choose ball diameter based on the Coupler rating.
2. The weight rating of the ball should match or exceed the trailer rating.
3. Install correct Hitch Ball so that the diameter matches the Coupler size:
 - The shank should be long enough to exceed the Ball Mount bar thickness and a tightened nut by 2-1/2 threads.
 - The diameter of the shank should match the tongue hole diameter.
4. Torque nut with locking washer to 450 ft lbs.

IF YOU EXPERIENCE ANY PROBLEMS WITH YOUR TOWSMART PRODUCT DO NOT RETURN THE UNIT TO THE RETAILER FROM WHICH IT WAS PURCHASED. INSTEAD, PLEASE CALL 1-844-295-9215 FOR ASSISTANCE WITH ANY PROBLEMS. WARRANTY INFORMATION IS AVAILABLE UPON REQUEST AND CAN BE FOUND ONLINE AT WWW.TOWSMART.COM.

HITCH BALL WITH 1-1/4" SHANK

INSTALLATION INSTRUCTIONS


⚠ WARNING: Read and observe all warnings, instructions, and capacity limitations before using this product. Failure to comply with this warning and the associated instructions and capacity limitations may result in serious personal injury and/or significant property damage.

1. Choose ball diameter based on the Coupler rating.
2. The weight rating of the ball should match or exceed the trailer rating.
3. Install correct Hitch Ball so that the diameter matches the Coupler size:
 - The shank should be long enough to exceed the Ball Mount bar thickness and a tightened nut by 2-1/2 threads.
 - The diameter of the shank should match the tongue hole diameter.
4. Torque nut with locking washer to 450 ft lbs.

IF YOU EXPERIENCE ANY PROBLEMS WITH YOUR TOWSMART PRODUCT DO NOT RETURN THE UNIT TO THE RETAILER FROM WHICH IT WAS PURCHASED. INSTEAD, PLEASE CALL 1-844-295-9215 FOR ASSISTANCE WITH ANY PROBLEMS. WARRANTY INFORMATION IS AVAILABLE UPON REQUEST AND CAN BE FOUND ONLINE AT WWW.TOWSMART.COM.

HITCH BALL WITH 1-1/4" SHANK

INSTALLATION INSTRUCTIONS


 **WARNING:** Read and observe all warnings, instructions, and capacity limitations before using this product. Failure to comply with this warning and the associated instructions and capacity limitations may result in serious personal injury and/or significant property damage.

1. Choose ball diameter based on the Coupler rating.
2. The weight rating of the ball should match or exceed the trailer rating.
3. Install correct Hitch Ball so that the diameter matches the Coupler size:
 - The shank should be long enough to exceed the Ball Mount bar thickness and a tightened nut by 2-1/2 threads.
 - The diameter of the shank should match the tongue hole diameter.
4. Torque nut with locking washer to 450 ft lbs.

IF YOU EXPERIENCE ANY PROBLEMS WITH YOUR TOWSMART PRODUCT DO NOT RETURN THE UNIT TO THE RETAILER FROM WHICH IT WAS PURCHASED. INSTEAD, PLEASE CALL 1-844-295-9215 FOR ASSISTANCE WITH ANY PROBLEMS. WARRANTY INFORMATION IS AVAILABLE UPON REQUEST AND CAN BE FOUND ONLINE AT WWW.TOWSMART.COM.

HITCH BALL WITH 5/8" SHANK

INSTALLATION INSTRUCTIONS


 **WARNING:** Read and observe all warnings, instructions, and capacity limitations before using this product. Failure to comply with this warning and the associated instructions and capacity limitations may result in serious personal injury and/or significant property damage.

1. Choose ball diameter based on the Coupler rating.
2. The weight rating of the ball should match or exceed the trailer rating.
3. Install correct Hitch Ball so that the diameter matches the Coupler size:
 - The shank should be long enough to exceed the Ball Mount bar thickness and a tightened nut by 2-1/2 threads.
 - The diameter of the shank should match the tongue hole diameter.
4. Torque nut with locking washer to 100 ft lbs.

IF YOU EXPERIENCE ANY PROBLEMS WITH YOUR TOWSMART PRODUCT DO NOT RETURN THE UNIT TO THE RETAILER FROM WHICH IT WAS PURCHASED. INSTEAD, PLEASE CALL 1-844-295-9215 FOR ASSISTANCE WITH ANY PROBLEMS. WARRANTY INFORMATION IS AVAILABLE UPON REQUEST AND CAN BE FOUND ONLINE AT WWW.TOWSMART.COM.

HITCH BALL WITH 1" SHANK

INSTALLATION INSTRUCTIONS


 **WARNING:** Read and observe all warnings, instructions, and capacity limitations before using this product. Failure to comply with this warning and the associated instructions and capacity limitations may result in serious personal injury and/or significant property damage.

1. Choose ball diameter based on the Coupler rating.
2. The weight rating of the ball should match or exceed the trailer rating.
3. Install correct Hitch Ball so that the diameter matches the Coupler size:
 - The shank should be long enough to exceed the Ball Mount bar thickness and a tightened nut by 2-1/2 threads.
 - The diameter of the shank should match the tongue hole diameter.
4. Torque nut with locking washer to 250 ft lbs.

IF YOU EXPERIENCE ANY PROBLEMS WITH YOUR TOWSMART PRODUCT DO NOT RETURN THE UNIT TO THE RETAILER FROM WHICH IT WAS PURCHASED. INSTEAD, PLEASE CALL 1-844-295-9215 FOR ASSISTANCE WITH ANY PROBLEMS. WARRANTY INFORMATION IS AVAILABLE UPON REQUEST AND CAN BE FOUND ONLINE AT WWW.TOWSMART.COM.

HITCH BALL WITH 1" SHANK

INSTALLATION INSTRUCTIONS

 **WARNING:** Read and observe all warnings, instructions, and capacity limitations before using this product. Failure to comply with this warning and the associated instructions and capacity limitations may result in serious personal injury and/or significant property damage.

1. Choose ball diameter based on the Coupler rating.
2. The weight rating of the ball should match or exceed the trailer rating.
3. Install correct Hitch Ball so that the diameter matches the Coupler size:
 - The shank should be long enough to exceed the Ball Mount bar thickness and a tightened nut by 2-1/2 threads.
 - The diameter of the shank should match the tongue hole diameter.
4. Torque nut with locking washer to 250 ft lbs.

IF YOU EXPERIENCE ANY PROBLEMS WITH YOUR TOWSMART PRODUCT DO NOT RETURN THE UNIT TO THE RETAILER FROM WHICH IT WAS PURCHASED. INSTEAD, PLEASE CALL 1-844-295-9215 FOR ASSISTANCE WITH ANY PROBLEMS. WARRANTY INFORMATION IS AVAILABLE UPON REQUEST AND CAN BE FOUND ONLINE AT WWW.TOWSMART.COM.

HITCH BALL WITH 1" SHANK

INSTALLATION INSTRUCTIONS


⚠ WARNING: Read and observe all warnings, instructions, and capacity limitations before using this product. Failure to comply with this warning and the associated instructions and capacity limitations may result in serious personal injury and/or significant property damage.

1. Choose ball diameter based on the Coupler rating.
2. The weight rating of the ball should match or exceed the trailer rating.
3. Install correct Hitch Ball so that the diameter matches the Coupler size:
 - The shank should be long enough to exceed the Ball Mount bar thickness and a tightened nut by 2-1/2 threads.
 - The diameter of the shank should match the tongue hole diameter.
4. Torque nut with locking washer to 250 ft lbs.

IF YOU EXPERIENCE ANY PROBLEMS WITH YOUR TOWSMART PRODUCT DO NOT RETURN THE UNIT TO THE RETAILER FROM WHICH IT WAS PURCHASED. INSTEAD, PLEASE CALL 1-844-295-9215 FOR ASSISTANCE WITH ANY PROBLEMS. WARRANTY INFORMATION IS AVAILABLE UPON REQUEST AND CAN BE FOUND ONLINE AT WWW.TOWSMART.COM.

HITCH BALL WITH 1-1/4" SHANK

INSTALLATION INSTRUCTIONS

 **WARNING:** Read and observe all warnings, instructions, and capacity limitations before using this product. Failure to comply with this warning and the associated instructions and capacity limitations may result in serious personal injury and/or significant property damage.

1. Choose ball diameter based on the Coupler rating.
2. The weight rating of the ball should match or exceed the trailer rating.
3. Install correct Hitch Ball so that the diameter matches the Coupler size:
 - The shank should be long enough to exceed the Ball Mount bar thickness and a tightened nut by 2-1/2 threads.
 - The diameter of the shank should match the tongue hole diameter.
4. Torque nut with locking washer to 450 ft lbs.

IF YOU EXPERIENCE ANY PROBLEMS WITH YOUR TOWSMART PRODUCT DO NOT RETURN THE UNIT TO THE RETAILER FROM WHICH IT WAS PURCHASED. INSTEAD, PLEASE CALL 1-844-295-9215 FOR ASSISTANCE WITH ANY PROBLEMS. WARRANTY INFORMATION IS AVAILABLE UPON REQUEST AND CAN BE FOUND ONLINE AT WWW.TOWSMART.COM.