

MAJOR TECHNICAL SPECIFICATIONS

Item				Area				U.S.A. and Canada							
Body Type				Regular Cab (2WD)				Extra Cab (2WD)							
Vehicle Grade				—, SR5 ^{*5}											
Model Code				RZN140L-TRMDKAB		RZN140L-TRPDKAB		RZN150L-CRMDKAB		RZN150L-CRPDKAB					
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4540 (178.7), 4685 (184.4)* ³		4540 (178.7), 4685 (184.4)* ³		5010 (197.2), 5155 (203.0)* ³		5010 (197.2), 5155 (203.0)* ³		5			
		Width	mm (in.)	1690 (66.5)		1690 (66.5)		1690 (66.5)		1690 (66.5)					
		Height	mm (in.)	1630 (64.2)* ¹ , 1620 (63.8)* ^{1, *2}		1625 (64.0)* ¹ , 1615 (63.6)* ^{1, *2}		1615 (63.6)* ¹ , 1605 (63.2)* ^{1, *2}		1615 (63.6)* ¹ , 1605 (63.2)* ^{1, *2}					
	Wheel Base		mm (in.)	2625 (103.3)		2625 (103.3)		3095 (121.9)		3095 (121.9)					
	Tread	Front	mm (in.)	1450 (57.1)		1450 (57.1)		1450 (57.1)		1450 (57.1)					
		Rear	mm (in.)	1455 (57.3)		1455 (57.3)		1455 (57.3)		1455 (57.3)		10			
	Effective Head Room	Front	mm (in.)	979 (38.5)		979 (38.5)		984 (38.7), 971 (38.2)* ⁴		984 (38.7), 971 (38.2)* ⁴					
		Rear	mm (in.)	—		—		884 (34.8)		884 (34.8)					
	Effective Leg Room	Front	mm (in.)	1059 (41.7)		1059 (41.7)		1088 (42.8)		1088 (42.8)					
		Rear	mm (in.)	—		—		690 (27.2)		690 (27.2)					
	Shoulder Room	Front	mm (in.)	1369 (53.9)		1369 (53.9)		1371 (54.0)		1371 (54.0)		15			
		Rear	mm (in.)	—		—		1329 (52.3)		1329 (52.3)					
	Cargo Space	Length	mm (in.)	—		—		—		—					
		Width	mm (in.)	—		—		—		—					
		Height	mm (in.)	—		—		—		—					
	Overhang	Front	mm (in.)	820 (32.3)		820 (32.3)		820 (32.3)		820 (32.3)		20			
		Rear	mm (in.)	1095 (43.1), 1240 (48.8)* ³		1095 (43.1), 1240 (48.8)* ³		1095 (43.1), 1240 (48.8)* ³		1095 (43.1), 1240 (48.8)* ³					
	Min. Running Ground Clearance		mm (in.)	215 (8.5), 205 (8.1)* ²		215 (8.5), 205 (8.1)* ²		215 (8.5), 205 (8.1)* ²		215 (8.5), 205 (8.1)* ²					
	Angle of Approach		degrees	24°, 23°* ²		24°, 23°* ²		24°, 23°* ²		24°, 23°* ²					
	Angle of Departure		degrees	28°, 20°* ³		28°, 20°* ³		26°, 19°* ³		26°, 19°* ³					
	Curb Mass.	Front	kg (lb)	728 (1605)		737 (1625)		778 (1715)		787 (1735)		25			
		Rear	kg (lb)	530 (1170)		531 (1170)		572 (1260)		572 (1260)					
		Total	kg (lb)	1259 (2775)		1268 (2795)		1349 (2975)		1359 (2995)					
	Gross Vehicle Mass.	Front	kg (lb)	—		—		—		—					
		Rear	kg (lb)	—		—		—		—					
		Total	kg (lb)	1925 (4250)		1925 (4250)		2040 (4500)		2040 (4500)		30			
	Fuel Tank Capacity		L (U.S.gal., Imp.gal.)	60.6 (160, 13.3)		60.6 (160, 13.3)		60.6 (160, 13.3)		60.6 (160, 13.3)					
	Luggage Compartment Capacity		m ³ (cu.ft.)	—		—		—		—					
Performance	Max. Speed		km/h (mph)	165 (103)		165 (103)		165 (103)		165 (103)					
	Max. Cruising Speed		km/h (mph)	—		—		—		—					
	Max. Permissible Speed	1st Gear	km/h (mph)	48 (30)		64 (40)		48 (30)		64 (40)		35			
		2nd Gear	km/h (mph)	89 (55)		122 (76)		89 (55)		122 (76)					
		3rd Gear	km/h (mph)	137 (85)		165 (103)		137 (85)		165 (103)					
		4th Gear	km/h (mph)	165 (103)		—		165 (103)		—					
	Turning Diameter (Outside Front)	Wall to Wall	m (ft.)	11.6 (38.1)		11.6 (38.1)		13.2 (43.3)		13.2 (43.3)		40			
Curb to Curb		m (ft.)	11.2 (36.7)		11.2 (36.7)		12.7 (41.7)		12.7 (41.7)						
Engine	Engine Type		2RZ-FE		2RZ-FE		2RZ-FE		2RZ-FE						
	Valve Mechanism		16-Valve, DOHC		16-Valve, DOHC		16-Valve, DOHC		16-Valve, DOHC						
	Bore × Stroke		mm (in.)	95.0 × 86.0 (3.74 × 3.39)		95.0 × 86.0 (3.74 × 3.39)		95.0 × 86.0 (3.74 × 3.39)		95.0 × 86.0 (3.74 × 3.39)					
	Displacement		cm ³ (cu.in.)	2438 (148.8)		2438 (148.8)		2438 (148.8)		2438 (148.8)					
	Compression Ratio			9.5 : 1		9.5 : 1		9.5 : 1		9.5 : 1		45			
	Carburetor Type			SFI		SFI		SFI		SFI					
	Research Octane No.		RON	91 or more		91 or more		91 or more		91 or more					
	Max. Output (SAE-NET)		kW/rpm (HP@rpm)	106 / 5000 (142@5000)		106 / 5000 (142@5000)		106 / 5000 (142@5000)		106 / 5000 (142@5000)					
Max. Torque (SAE-NET)		N·m/rpm (lb-ft@rpm)	217 / 4000 (160@4000)		217 / 4000 (160@4000)		217 / 4000 (160@4000)		217 / 4000 (160@4000)						
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12–48, 12–55* ⁵		12–48, 12–55* ⁵		12–55		12–55		50			
	Alternator Output		Watts	960		960		960		960					
	Starter Output		kW	1.4		1.4		1.4		1.4					
Chassis	Clutch Type		Dry, Single, Diaphragm				Dry, Single, Diaphragm				—				
	Transmission Type		W59				A44D				W59		A44D		
	Transmission Gear Ratio	In First	3.954		2.826		3.954		2.826				55		
		In Second	2.141		1.493		2.141		1.493						
		In Third	1.384		1.000		1.384		1.000						
		In Fourth	1.000		0.688		1.000		0.688						
		In Fifth	0.810		—		0.810		—						
		In Reverse	4.091		2.703		4.091		2.703				60		
	Transfer Gear Ratio H4/H2		—				—				—				
	Differential Gear Ratio (Front/Rear)		— / 3.583				— / 3.727				— / 3.583		— / 3.727		
	Differential Gear Size (Front/Rear)		in.	— / 7.5"				— / 7.5"				— / 7.5"			
	Brake Type	Front	Ventilated Disc				Ventilated Disc				Ventilated Disc				
		Rear	Leading-Trailing Drum				Leading-Trailing Drum				Leading-Trailing Drum				65
	Parking Brake Type		Leading-Trailing Drum				Leading-Trailing Drum				Leading-Trailing Drum				
	Brake Booster Type and Size		in.	Single 10"				Single 10"				Single 10"			
	Proportioning Valve Type		LSP and BV				LSP and BV				LSP and BV				
	Suspension Type	Front	Double Wishbone, coil				Double Wishbone, coil				Double Wishbone, coil				
		Rear	Rigid Leaf				Rigid Leaf				Rigid Leaf				70
	Stabilizer Bar	Front	STD				STD				STD				
		Rear	—				—				—				
	Steering Gear Type		Rack and Pinion				Rack and Pinion				Rack and Pinion				
	Steering Gear Ratio (Overall)		22.3, 20.4* ⁷				22.3, 20.4* ⁷				22.3, 20.4* ⁷				
	Power Steering Type		Integral Type				Integral Type				Integral Type				75

*1: Unladen Vehicle

*2: With P235 / 70 R16 Tire

*3: With Rear Bumper

*4: With Moon Roof

*5: Option

*6: With ABS

*7: With Power Steering

*8: With P265 / 70 R16 Tire

U.S.A. and Canada						
Extra Cab (2WD)		Regular Cab (4WD)		Extra Cab (4WD)		
Sport		—, SR5*5, Limited*5				
VZN150L-CRMDKAB	RZN161L-TRMDKAB	RZN161L-TRPDKAB	RZN171L-CRMDKAB	RZN171L-CRPDKAB	VZN170L-CRMDKAB	
5155 (203.0)	4685 (184.4)	4685 (184.4)	5155 (203.0)	5155 (203.0)	5155 (203.0)	
1765 (69.5)	1690 (66.5), 1785 (70.3)*5	1690 (66.5), 1785 (70.3)*5	1690 (66.5), 1785 (70.3)*5	1690 (66.5), 1785 (70.3)*5	1690 (66.5), 1785 (70.3)*5	
1590 (62.6)*1	1720 (67.7)*1, 1750 (68.9)*1,*8	1720 (67.7)*1, 1750 (68.9)*1,*8	1715 (67.5)*1, 1745 (68.7)*1,*8	1715 (67.5)*1, 1745 (68.7)*1,*8	1715 (67.5)*1, 1745 (68.7)*1,*8	
3095 (121.9)	2625 (103.3)	2625 (103.3)	3095 (121.9)	3095 (121.9)	3095 (121.9)	
1450 (57.1)	1460 (57.5), 1500 (59.1)*5	1460 (57.5), 1500 (59.1)*5	1460 (57.5), 1500 (59.1)*5	1460 (57.5), 1500 (59.1)*5	1460 (57.5), 1500 (59.1)*5	
1455 (57.3)	1455 (57.3), 1495 (58.9)*5	1455 (57.3), 1495 (58.9)*5	1455 (57.3), 1495 (58.9)*5	1455 (57.3), 1495 (58.9)*5	1455 (57.3), 1495 (58.9)*5	
984 (38.7), 971 (38.2)*4	979 (38.5)	979 (38.5)	984 (38.7), 971 (38.2)*4	984 (38.7), 971 (38.2)*4	984 (38.7), 971 (38.2)*4	
884 (34.8)	—	—	884 (34.8)	884 (34.8)	884 (34.8)	
1088 (42.8)	1059 (41.7)	1059 (41.7)	1088 (42.8)	1088 (42.8)	1088 (42.8)	
690 (27.2)	—	—	690 (27.2)	690 (27.2)	690 (27.2)	
1371 (54.0)	1369 (53.9)	1369 (53.9)	1371 (54.0)	1371 (54.0)	1371 (54.0)	
1329 (52.3)	—	—	1329 (52.3)	1329 (52.3)	1329 (52.3)	
—	—	—	—	—	—	
—	—	—	—	—	—	
—	—	—	—	—	—	
820 (32.3)	820 (32.3)	820 (32.3)	820 (32.3)	820 (32.3)	820 (32.3)	
1240 (48.8)	1240 (48.8)	1240 (48.8)	1240 (48.8)	1240 (48.8)	1240 (48.8)	
195 (7.7)	280 (11.0), 305 (12.0)*8	280 (11.0), 305 (12.0)*8	275 (10.8), 305 (12.0)*8	275 (10.8), 305 (12.0)*8	275 (10.8), 305 (12.0)*8	
23°	32°, 35°*8	32°, 35°*8	32°, 35°*8	32°, 35°*8	32°, 35°*8	
19°	24°, 26°*8	24°, 26°*8	24°, 26°*8	24°, 26°*8	24°, 26°*8	
814 (1795)	885 (1950)	898 (1980)	932 (2055)	946 (2085)	957 (2110)	
615 (1355)	624 (1375)	624 (1375)	658 (1450)	658 (1450)	653 (1440)	
1429 (3150)	1508 (3325)	1522 (3355)	1590 (3505)	1603 (3535)	1610 (3550)	
—	—	—	—	—	—	
—	—	—	—	—	—	
2040 (4500)	2315 (5100)	2315 (5100)	2315 (5100)	2315 (5100)	2315 (5100)	
60.6 (160, 13.3)	70.0 (18.5, 15.4)	70.0 (18.5, 15.4)	70.0 (18.5, 15.4)	70.0 (18.5, 15.4)	70.0 (18.5, 15.4)	
—	—	—	—	—	—	
180 (112)	165 (103)	165 (103)	165 (103)	165 (103)	165 (103)	
—	—	—	—	—	—	
54 (34)	46 (29)	62 (39)	46 (29)	62 (39)	47 (29)	
101 (63)	85 (53)	113 (70)	85 (53)	113 (70)	88 (55)	
146 (91)	132 (82)	165 (103)	132 (82)	165 (103)	127 (79)	
180 (112)	165 (103)	—	165 (103)	—	165 (103)	
13.2 (43.3)	11.2 (36.7)	11.2 (36.7)	12.9 (42.3)	12.9 (42.3)	12.9 (42.3)	
12.7 (41.7)	10.5 (34.4)	10.5 (34.4)	12.2 (40.0)	12.2 (40.0)	12.2 (40.0)	
5VZ-FE	3RZ-FE	3RZ-FE	3RZ-FE	3RZ-FE	5VZ-FE	
24-Valve, DOHC	16-Valve, DOHC	16-Valve, DOHC	16-Valve, DOHC	16-Valve, DOHC	24-Valve, DOHC	
93.5 × 82.0 (3.68 × 3.23)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	93.5 × 82.0 (3.68 × 3.23)	
3378 (206.1)	2694 (164.3)	2694 (164.3)	2694 (164.3)	2694 (164.3)	3378 (206.1)	
9.6 : 1	9.5 : 1	9.5 : 1	9.5 : 1	9.5 : 1	9.6 : 1	
SFI	SFI	SFI	SFI	SFI	SFI	
91 or more	91 or more	91 or more	91 or more	91 or more	91 or more	
142 / 4800 (190@4800)	112 / 4800 (150@4800)	112 / 4800 (150@4800)	112 / 4800 (150@4800)	112 / 4800 (150@4800)	142 / 4800 (190@4800)	
298 / 3600 (220@3600)	240 / 4000 (177@4000)	240 / 4000 (177@4000)	240 / 4000 (177@4000)	240 / 4000 (177@4000)	298 / 3600 (220@3600)	
12–55	12–55	12–55	12–55	12–55	12–55	
960	960	960	960	960	960	
1.4	1.4, 2.0*5	1.4, 2.0*5	1.4, 2.0*5	1.4, 2.0*5	1.4	
Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	
R150	W59	A340F	W59	A340F	R150F	
3.830	3.954	2.804	3.954	2.804	3.830	
2.062	2.141	1.531	2.141	1.531	2.062	
1.436	1.384	1.000	1.384	1.000	1.436	
1.000	1.000	0.705	1.000	0.705	1.000	
0.838	0.810	—	0.810	—	0.838	
4.220	4.091	2.393	4.091	2.393	4.220	
—	1000 / 2.566	1000 / 2.566	1000 / 2.566	1000 / 2.566	1000 / 2.566	
— / 3.153	3.909 / 3.909, 4.300 / 4.300*8	4.100 / 4.100, 4.555 / 4.555*8	3.909 / 3.909, 4.300 / 4.300*8	4.100 / 4.100, 4.555 / 4.555*8	3.909 / 3.909, 4.100 / 4.100*8	
— / 8"	7.5" / 8"	7.5" / 8"	7.5" / 8"	7.5" / 8"	7.5" / 8"	
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	
Leading-Trailing Drum	Leading-Trailing Drum	Leading-Trailing Drum	Leading-Trailing Drum	Leading-Trailing Drum	Leading-Trailing Drum	
Leading-Trailing Drum	Leading-Trailing Drum	Leading-Trailing Drum	Leading-Trailing Drum	Leading-Trailing Drum	Leading-Trailing Drum	
Single 10"	Single 10"	Single 10"	Single 10"	Single 10"	Single 10"	
LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	
Double Wishbone, coil	Double Wishbone, coil	Double Wishbone, coil	Double Wishbone, coil	Double Wishbone, coil	Double Wishbone, coil	
Rigid Leaf	Rigid Leaf	Rigid Leaf	Rigid Leaf	Rigid Leaf	Rigid Leaf	
STD	STD	STD	STD	STD	STD	
—	—	—	—	—	—	
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	
20.4	19.4	19.4	19.4	19.4	19.4	
Integral Type	Integral Type	Integral Type	Integral Type	Integral Type	Integral Type	

Item			Area		U.S.A. and Canada			
Body Type					Extra Cab (4WD)	Double Cab (4WD)	Regular Cab (Pre Runner)	Extra Cab (Pre Runner)
Vehicle Grade					—, SR5*3, Limited*5		—, SR5*3	
Model Code					VZN170L-CRPDKAB	VZN170L-PRPKAB	RZN191L-TRPKAB	RZN196L-CRPDKAB
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5155 (203.0)	5155 (203.0)	4685 (184.4)	5155 (203.0)	5
		Width	mm (in.)	1690 (66.5), 1785 (70.3)*5	1785 (70.3)	1690 (66.5), 1785 (70.3)*5	1690 (66.5), 1785 (70.3)*5	
		Height	mm (in.)	1715 (67.5)*1, 1745 (68.7)*1,*8	1715 (67.5)*1, 1745 (68.7)*1,*8,*9	1720 (67.7)*1, 1750 (68.9)*1,*8	1715 (67.5)*1, 1745 (68.7)*1,*8	
	Wheel Base		mm (in.)	3095 (121.9)	3095 (121.9)	2625 (103.3)	3095 (121.9)	
	Tread	Front	mm (in.)	1460 (57.5), 1500 (59.1)*5	1460 (57.5), 1500 (59.1)*5	1460 (57.5), 1500 (59.1)*5	1460 (57.5), 1500 (59.1)*5	
		Rear	mm (in.)	1455 (57.3), 1495 (58.9)*5	1455 (57.3), 1495 (58.9)*5	1455 (57.3), 1495 (58.9)*5	1455 (57.3), 1495 (58.9)*5	10
	Effective Head Room	Front	mm (in.)	984 (38.7), 971 (38.2)*4	988 (38.9), 981 (38.6)*1	979 (38.5)	984 (38.7), 971 (38.2)*4	
		Rear	mm (in.)	884 (34.8)	961 (37.8)	—	884 (34.8)	
	Effective Leg Room	Front	mm (in.)	1088 (42.8)	1088 (42.8)	1059 (41.7)	1088 (42.8)	
		Rear	mm (in.)	690 (27.2)	858 (33.8)	—	690 (27.2)	
	Shoulder Room	Front	mm (in.)	1371 (54.0)	1371 (54.0)	1369 (53.9)	1371 (54.0)	15
		Rear	mm (in.)	1329 (52.3)	1360 (53.5)	—	1329 (52.3)	
	Cargo Space	Length	mm (in.)	—	—	—	—	
		Width	mm (in.)	—	—	—	—	
		Height	mm (in.)	—	—	—	—	
	Overhang	Front	mm (in.)	820 (32.3)	820 (32.3)	820 (32.3)	820 (32.3)	20
		Rear	mm (in.)	1240 (48.8)	1240 (48.8)	1240 (48.8)	1240 (48.8)	
	Min. Running Ground Clearance		mm (in.)	275 (10.8), 305 (12.0)*8	255 (10.0), 285 (11.2)	280 (11.0), 305 (12.0)*8	275 (10.8), 305 (12.0)*8	
	Angle of Approach		degrees	32°, 35°*8	30°, 33°*8	32°, 35°*8	32°, 35°*8	
	Angle of Departure		degrees	24°, 26°*8	23°, 25°*8	24°, 26°*8	24°, 26°*8	
	Curb Mass.	Front	kg (lb)	968 (2135)	996 (2195)	807 (1780)	853 (1880)	25
		Rear	kg (lb)	653 (1440)	701 (1545)	612 (1350)	646 (1425)	
		Total	kg (lb)	1622 (3575)	1696 (3740)	1420 (3130)	1499 (3505)	
	Gross Vehicle Mass.	Front	kg (lb)	—	—	—	—	
		Rear	kg (lb)	—	—	—	—	
		Total	kg (lb)	2315 (5100)	2315 (5100)	2315 (5100)	2315 (5100)	30
	Fuel Tank Capacity		L (U.S.gal., Imp.gal.)	70.0 (18.5, 15.4)	70.0 (18.5, 15.4)	70.0 (18.5, 15.4)	70.0 (18.5, 15.4)	
	Luggage Compartment Capacity		m ³ (cu.ft.)	—	—	—	—	
Performance	Max. Speed		km/h (mph)	165 (103)	165 (103)	165 (103)	165 (103)	
	Max. Cruising Speed		km/h (mph)	—	—	—	—	
	Max. Permissible Speed	1st Gear	km/h (mph)	65 (40)	65 (40)	65 (40)	62 (39)	35
		2nd Gear	km/h (mph)	119 (74)	119 (74)	119 (74)	113 (70)	
		3rd Gear	km/h (mph)	165 (103)	165 (103)	165 (103)	165 (103)	
		4th Gear	km/h (mph)	—	—	—	—	
	Turning Diameter (Outside Front)	Wall to Wall	m (ft.)	12.9 (42.3)	12.9 (42.3)	11.2 (36.7)	12.9 (42.3)	40
		Curb to Curb	m (ft.)	12.2 (40.0)	12.2 (40.0)	10.5 (34.4)	12.2 (40.0)	
Engine	Engine Type			5VZ-FE	5VZ-FE	3RZ-FE	3RZ-FE	
	Valve Mechanism			24-Valve, DOHC	24-Valve, DOHC	16-Valve, DOHC	16-Valve, DOHC	
	Bore × Stroke		mm (in.)	93.5 × 82.0 (3.68 × 3.23)	93.5 × 82.0 (3.68 × 3.23)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	
	Displacement		cm ³ (cu.in.)	3378 (206.1)	3378 (206.1)	2694 (164.3)	2694 (164.3)	
	Compression Ratio			9.6 : 1	9.6 : 1	9.5 : 1	9.5 : 1	45
	Carburetor Type			SFI	SFI	SFI	SFI	
	Research Octane No.		RON	91 or more	91 or more	91 or more	91 or more	
	Max. Output (SAE-NET)		kW/rpm (HP@rpm)	142 / 4800 (190@4800)	142 / 4800 (190@4800)	112 / 4800 (150@4800)	112 / 4800 (190@4800)	
	Max. Torque (SAE-NET)		N·m/rpm (lb-ft@rpm)	298 / 3600 (220@3600)	298 / 3600 (220@3600)	240 / 4000 (177@4000)	240 / 4000 (177@4000)	
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12-55	12-55	12-55	12-55	50
	Alternator Output		Watts	960	960	960	960	
	Starter Output		kW	1.4, 1.8*5	1.4, 1.8*5	1.4, 2.0*5	1.4, 2.0*5	
Chassis	Clutch Type			—	—	—	—	
	Transmission Type			A340F	A340F	A340E	A340E	55
	Transmission Gear Ratio	In First		2.804	2.804	2.804	2.804	
		In Second		1.531	1.531	1.531	1.531	
		In Third		1.000	1.000	1.000	1.000	
		In Fourth		0.705	0.705	0.705	0.705	
		In Fifth		—	—	—	—	
		In Reverse		2.393	2.393	2.393	2.393	60
	Transfer Gear Ratio H4/H2			1.000 / 2.566	1.000 / 2.566	—	—	
	Differential Gear Ratio (Front/Rear)			3.909 / 3.909, 4.100 / 4.100*8	3.909 / 3.909, 4.100 / 4.100*8	— / 3.909, 4.300*8	— / 4.100, 4.555*8	
	Differential Gear Size (Front/Rear)		in.	7.5" / 8"	7.5" / 8"	— / 8"	— / 8"	
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	
		Rear		Leading-Trailing Drum	Leading-Trailing Drum	Leading-Trailing Drum	Leading-Trailing Drum	65
	Parking Brake Type			Leading-Trailing Drum	Leading-Trailing Drum	Leading-Trailing Drum	Leading-Trailing Drum	
	Brake Booster Type and Size		in.	Single 10"	Single 10"	Single 10"	Single 10"	
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV	
	Suspension Type	Front		Double Wishbone, Coil	Double Wishbone, Coil	Double Wishbone, Coil	Double Wishbone, Coil	
Rear			Rigid Leaf	Rigid Leaf	Rigid Leaf	Rigid Leaf	70	
Stabilizer Bar	Front		STD	STD	STD	STD		
	Rear		—	—	—	—		
Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion		
Steering Gear Ratio (Overall)			19.4	19.4	19.4	19.4		
Power Steering Type			Integral Type	Integral Type	Integral Type	Integral Type	75	

*1: Unladen Vehicle

*2: With P235 / 70 R16 Tire

*3: With Rear Bumper

*4: With Moon Roof

*5: Option

*6: With ABS

*7: With Power Steering

*8: With P265 / 70 R16 Tire

*9: With Roof-Rack: +65 mm (2.6 in.)

U.S.A. and Canada			
	Double Cab (Pre Runner)	Extra Cab (Pre Runner)	Double Cab (Pre Runner)
	—, SR5*5		
	RZN196L-PRPKAB	VZN195L-CRPDKAB	VZN195L-PRPKAB
5	5155 (203.0)	5155 (203.0)	5155 (203.0)
	1785 (70.3)	1690 (66.5), 1785 (70.3)*5	1785 (70.3)
	1715 (67.5)*1,*9, 1745 (68.7)*1,*8,*9	1720 (67.7)*1, 1750 (68.9)*1,*8	1715 (67.5)*1,*9, 1745 (68.7)*1,*8,*9
	3095 (121.9)	3095 (121.9)	3095 (121.9)
	1460 (57.5), 1500 (59.1)*5	1460 (57.5), 1500 (59.1)*5	1460 (57.5), 1500 (59.1)*5
10	1455 (57.3), 1495 (58.9)*5	1455 (57.3), 1495 (58.9)*5	1455 (57.3), 1495 (58.9)*5
	998 (38.9), 981 (38.6)*4	984 (38.7), 971 (38.2)*4	988 (38.9), 981 (38.6)*4
	961 (37.8)	884 (34.8)	961 (37.8)
	1088 (42.8)	1088 (42.8)	1088 (42.8)
	858 (33.8)	690 (27.2)	858 (33.8)
15	1371 (54.0)	1371 (54.0)	1371 (54.0)
	1360 (53.5)	1329 (52.3)	1360 (53.5)
	—	—	—
	—	—	—
	—	—	—
20	820 (32.3)	820 (32.3)	820 (32.3)
	1240 (48.8)	1240 (48.8)	1240 (48.8)
	255 (10.0), 285 (11.2)*8	275 (10.8), 305 (12.0)*8	255 (10.0), 285 (11.2)*8
	30°, 33°*8	32°, 35°*8	30°, 33°*8
	23°, 25°*8	24°, 26°*8	23°, 25°*8
25	878 (1935)	878 (1935)	902 (1990)
	694 (1530)	642 (1415)	689 (1520)
	1572 (3465)	1520 (3350)	1592 (3510)
	—	—	—
	—	—	—
30	2315 (5100)	2315 (5100)	2315 (5100)
	70.0 (18.5, 15.4)	70.0 (18.5, 15.4)	70.0 (18.5, 15.4)
	—	—	—
	165 (103)	165 (103)	165 (103)
	—	—	—
35	62 (39)	65 (40)	65 (40)
	113 (70)	119 (74)	119 (74)
	165 (103)	165 (103)	165 (103)
	—	—	—
	12.9 (42.3)	12.9 (42.3)	12.9 (42.3)
40	12.2 (40.0)	12.2 (40.0)	12.2 (40.0)
	3RZ-FE	5VZ-FE	5VZ-FE
	16-Valve, DOHC	24-Valve, DOHC	24-Valve, DOHC
	95.0 × 95.0 (3.74 × 3.74)	93.5 × 82.0 (3.68 × 3.23)	93.5 × 82.0 (3.68 × 3.23)
	2694 (164.3)	3378 (206.1)	3378 (206.1)
45	9.5 : 1	9.6 : 1	9.6 : 1
	SFI	SFI	SFI
	91 or more	91 or more	91 or more
	112 / 4800 (150@4800)	142 / 4800 (190@4800)	142 / 4800 (190@4800)
	240 / 4000 (177@4000)	298 / 3600 (220@3600)	298 / 3600 (220@3600)
50	12-55	12-55	12-55
	960	960	960
	1.4, 2.0*5	1.4, 1.8*5	1.4, 1.8*5
	—	—	—
	A340E	A340E	A340E
55	2.804	2.804	2.804
	1.531	1.531	1.531
	1.000	1.000	1.000
	0.705	0.705	0.705
	—	—	—
60	2.393	2.393	2.393
	—	—	—
	— / 4.100, 4.555*8	— / 3.900, 4.100*2	— / 3.900, 4.100*2
	— / 8"	— / 8"	— / 8"
	Ventilated Disc	Ventilated Disc	Ventilated Disc
65	Leading-Trailing Drum	Leading-Trailing Drum	Leading-Trailing Drum
	Leading-Trailing Drum	Leading-Trailing Drum	Leading-Trailing Drum
	Single 10"	Single 10"	Single 10"
	LSP and BV	LSP and BV	LSP and BV
	Double Wishbone, Coil	Double Wishbone, Coil	Double Wishbone, Coil
70	Rigid Leaf	Rigid Leaf	Rigid Leaf
	STD	STD	STD
	—	—	—
	Rack and Pinion	Rack and Pinion	Rack and Pinion
	19.4	19.4	19.4
75	Integral Type	Integral Type	Integral Type