

INSTALLATION INSTRUCTIONS

LED WALL SCONCE

Please read carefully and save these instructions, as you may need them at a later date.

CAUTION

WARNING: Risk of Fire. Min 90°C supply conductors. Consult a qualified electrician to ensure correct branch circuit conductor. Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

ASSEMBLY AND INSTALLATION

1. Shut off the power at the circuit breaker and remove existing fixture, including the mounting hardware.
2. Remove the fixture mounting screw and mounting plate from the fixture.
3. Secure mounting ring to the outlet box using outlet box screws. Make sure the two mounting screw holes (Spacing 2-1/8") are horizontal.
4. Connect the fixture wires to supply wires as shown, making sure that all wire connectors are secured. connect the fixture's ground wire directly to the back plate using the green screw provided. After wires are connected, tuck them carefully inside the Outlet Box.
5. Secure mounting plate to the mounting ring two mounting holes using mounting screw. (horizontal and Spacing mounting holes 2-1/8") .Adjustable mobile mounting plate can be left or right to move to the appropriate position.
6. Place the fixture over the mounting plate, and secure it with fixture mounting screw.

DIMMING

This fixture features electronic Traic dimming capabilities. To utilize TRAIIC dimming: use wires black (hot), white (neutral) and bare copper ground wire (ground).

SELECTABLE COLOR TEMPERATURE

The lamp can switch between three color temperatures (3000k-4000k-5000k), which can be adjusted to your preference with the switch in the Back Plate.

