

www.vevor.com
 Contact:service@vevor.com
 Call us:
 (+626) 275-4507 (For USA)
 (+44) 1173182739 (For Europe)
 (+001) 626 275-4507
 (For Other Countries)
 Working Time:
 Mon-Fri 8:00 am to 5:00 pm



Attentions

- 1.Please read the manual carefully before using it.
- 2.Handle it carefully during operation, avoid throwing down or pressing it heavily.
- 3.If the users disassemble or deliberately damage the machine, it will beyond the warranty.
- 4.please keep distance from the system when charging
- 5.After being used, turn off the display and pull out all the connection joints.
- 6.Due to the version upgrades, if mentioned in this manual content does not accord with your machine, please refer to our machine.

Description

- 1.Color TFT LCD Screen.
- 2.High resolution camera,clear picture.
- 3.Night vision.
- 4.High quality special cable, waterproof and anti-corrosion/cold/tensile.
- 5.Lithium battery.
6. The lights can on/off.night lights adjustable.
- 7.Range of Application: Water-supply pipe, Air-conditioner pipe, Cable pipe, Pipeline vacuum system, PLUNBIN pipe, Buildings, Sunken pipe

Product Specification

Item:	parameter
Charger:	AC100-240V
Battery:	Lithium battery
Investigation depth:	10M(selectable line length)
Material:	Fiber tube with high intensity
Camera light source:	With high white light
Camera material:	Stainless steel
Menu languages:	Multi-language
Camera picture:	Color

Instruction for Product

1.Camera

- 1metal contact chip 2spring 3highlight white LED 4camera lens



Product Specification

Item:	parameter
Camera diameter:	17MM
Camera light source:	6 LED with high white light(adjustable)
Camera working voltage:	5V
Lights working voltage:	12V
Water proof:	IP68
Camera material:	stainless steel
Camera size:	100MM* 17MM
Camera protective cover parts material:	metal
Camera protective cover parts size:	20MM* 25MM

Product components and accessories



Charging

When the battery power is low, it needs charging, and the method is as below:
 1. Take out the battery and charger from the box.
 2. Connect the charger to the battery.
 3. Connect the charger to the alternating current of 100-240v. The red indicator means charging.
 4. The green indicator means finishing charging.
 Notes: to make sure the battery using age longer, please recharge it timely; otherwise, it will make it can not recharged.



5. Adjust LED light degree adjuster to proper light degree.
6. After utilization, mover the camera from the pipe carefully, take clean, soft and dry cloth to clear up it and put it back.

PRODUCT CONNECTION



2.Monitor (Recording Type)

HD 4.3inch LCD display with DVR Recording Function



How to operate the Monitor

1. Power On
Plug in the camera, then turn on the monitor
2. Menu Setting
A: Press the MENU button into the Menu setting in the photo or record state.
B: It has format, language Settings, default Settings and date Settings.
3. MODE
Photo, Record and file browsing mode can be converted each other when press MODE button.
4. OK Button

- A: Press OK button to take the photo in the photo state.
- B: In Record state, press OK button one time to start the recording, press OK button again to stop the recording and saving.
5. UP Button
A: Turn up LED
B: Press UP button one time to forward a picture or an video in file browsing mode.
- C: Press UP button one time to forward in menu setting mode.
6. Down Button
A: Turn down LED
B: Press Down button one time to downward a picture or an video in file browsing mode.
- C: Press Down button one time to downward in menu setting mode.

3 Coil



4.Install the monitor

INSTALLING THE MONITOR



System Installation

1. Vital: turn off the power switch, connect the video camera and the monitor, or the video camera and the monitor may be damaged.
2. Connect camera -coil -monitor .
3. Turn on the power switch in the power box, the switchboard starts.
4. Install the video camera with the protective cover slightly and put it