













# **VEVOR**

**Affordable. Reliable. Home Improvement.**

## **WHEEL CHOCK TIE-DOWN KIT**

**MODEL: XM0501/ XM0502/ XM0503/ XM0504/ XM0505/ XM0506/  
XM0507/ XM0508/ XM0509/ XM0510/ XM0511/ XM0512**

# VEVOR Support Center

1	<b>XM0501</b>		7	<b>XM0507</b>	
2	<b>XM0502</b>		8	<b>XM0508</b>	
3	<b>XM0503</b>		9	<b>XM0509</b>	
4	<b>XM0504</b>		10	<b>XM0510</b>	
5	<b>XM0505</b>		11	<b>XM0511</b>	
6	<b>XM0506</b>		12	<b>XM0512</b>	

# VEVOR

Affordable. Reliable. Home Improvement.

## WHEEL CHOCK TIE-DOWN KIT

MODEL: XM0501/ XM0502/ XM0503/ XM0504/ XM0505/ XM0506/  
XM0507/ XM0508/ XM0509 /XM0510/ XM0511/ XM0512



XM0501/ XM0502



XM0503



XM0504



XM0505/XM0506



XM0507



XM0508/XM0509/XM0510



XM0511




XM0512

This is the original instruction, please read all manual instructions carefully before operating. VEVOR reserves a clear interpretation of our user manual. The appearance of the product shall be subject to the product you received. Please forgive us that we won't inform you again if there are any technology or software updates on our product.



Warning-To reduce the risk of injury, user must read instructions manual carefully.

## SAFETY & WARNING



-  Read and understand this entire manual before assembling, installing, operating, or servicing this product. Failure to follow these warnings and instructions can cause death, personal injury or damage to valuable property.
- Do not overload the chock tie. Never exceed the maximum weight capacity of the parameter table.
- Make sure the vehicle's engine is OFF, with parking brake set, before bundling tires or other car parts.
- The performance of the Wheel Stabilizer is dependent on proper trailer tire pressures. Check tire pressures frequently for safety, good tire wear and good chock performance.
- Adhere to all Department of Transportation (D.O.T.) requirements when using this product.
- Use common sense when working. Stay alert and concentrate when setting up and using this product. Never work while under the influence of alcohol, drugs or medications.
- While assembling and using this product keep work area clean and well-lit. Keep spectators and children out of the work area.
- Dress appropriately. Never wear loose fitting clothing or jewelry when working. Contain long hair, and keep hair, clothing and gloves away from moving parts.












## PRODUCT PARAMETERS


Model	load capacity/lbs
XM0501/XM0502	3333
XM0503	550
XM0504/ XM0505/ XM0506/ XM0507/ XM0508/ XM0509/ XM0510	3333
XM0511/ XM0512	1460

## ACCESSORIES LIST

Model	Parts Name	Picture	Quantity
XM0501/ XM0502	8-inch spring hook ratchet tire straps		4
	36-inch (approx. 91.4 cm) axle straps		4
	24-inch (approx. 61.4 cm) axle straps		4
	tensioners		4
	zipper storage bag		1
XM0503	Tensioners		2





	Screw sets		4
	Connectors		2
XM0504	Tensioners with double J-shaped hooks		4
	Webbing with 3 sliding rubber blocks		4
	Zipper storage bag		1
XM0505/ XM0506	Tensioners and D-rings		4
	Flat hooks and lariat-style shoulder straps		4
	Zipper storage bag		1
M0507	Zipper storage bag		1
	Solid ratchets with spring hooks		4
	Tire straps		4
	Axle straps		4

XM0508/ XM0509/ XM0510	Zipper storage bag		1
	Solid ratchets with heavy-duty hooks		4
	Tire straps with rings		4
XM0511	Storage bag		1
	Ratchet straps with E-hooks		2
	Wheel chocks		4
	Straps		2
	M6*60 screws + nuts		24
XM0512	Storage bag		1
	Ratchet straps with E-hooks		4
	Wheel chocks		8





	Straps		4
	M6*60 screws + nuts		48

## INSTALLATION STEPS

### A. Ratchet instructions

<p><b>STEP 1</b></p> 	<p>From bottom, thread webbing through slot in center of the spool of closed ratchet.</p>
<p><b>STEP 2</b></p> 	<p>Pull webbing through, removing the slack.</p>
<p><b>STEP 3</b></p> 	<p>Start ratcheting--raising and lowering handle.</p>
<p><b>STEP 4</b></p> 	<p>Finish ratcheting with lowered handle.</p>

## B. Release instructions

<p><b>STEP 1</b></p>  <p>release tab</p>	<p>Pull&amp;hold release tab(to override ratcheting function).</p>
<p><b>STEP 2</b></p> 	<p>Open ratchet until it is completely open and flat.</p>
<p><b>STEP 3</b></p> 	<p>Remove webbing from ratchet by gently pulling it out.</p>
<p><b>STEP 4</b></p> 	<p>Pull and hold release tab to close ratchet.</p>

## Usage scenario



Atv Transport



Road Rescue

**Manufacturer:** Shanghaimuxinmuyeyouxiangongsi

**Address:** Shuangchenglu 803nong11hao1602A-1609shi, baoshanqu, shanghai 200000 CN.

**Imported to AUS:** SIHAO PTY LTD. 1 ROKEVA STREETEASTWOOD NSW 2122 Australia

**Imported to USA:** Sanven Technology Ltd. Suite 250, 9166 Anaheim Place, Rancho Cucamonga, CA 91730

<b>UK</b>	<b>REP</b>
-----------	------------

YH CONSULTING LIMITED. C/O YH Consulting Limited Office 147, Centurion House, London Road, Staines-upon-Thames, Surrey, TW18 4AX

<b>EC</b>	<b>REP</b>
-----------	------------

E-CrossStu GmbH  
Mainzer Landstr.69,  
60329 Frankfurt am Main.

